

8*10/100/1000Base-T + 4*1000Base-X SFP

Industrial Ethernet Switch

LT-IS6012G-4GX8GT



Features:

- 8*10/100/1000Base-T RJ45 ports, 4*1000Base-X SFP slots
- DC 12-58V input, redundant power supply with polarity reverse/over-voltage/over current protection
- Support one channel output relay alarm (terminal block Pin 5/6)
- Support powerful Dip switch function:
 - 1. Link aggregation; 2. Flow control; 3. QoS(1-2 ports) ; 4. Broadcast storm restrain
- Support 10K Bytes Jumbo frame
- Support 6KV surge protection and ESD: Air-15kV, Contact-8kV Protection
- IP40 fan-less and Din-rail hardware design
- Operation temperature: -40 °C ~+75 °C

Overview

The SmartByte LT-IS6012G-4GX8GT is the highly reliable industrial Ethernet switch with 8-port 10/100/1000-T RJ45 and 4-port 1000Base-X SFP slots. It is featuring with port isolation, flow control, QoS(1-2 ports) and broadcast storm function, which all can be configured by the Dip switch on the top panel

LT-IS6012G-4GX8GT is a high cost-effective easy-to-use device, which provides essential industrial Ethernet networking function, including wide range power input 12-58VDC, redundant power design with polarity reverse/over-voltage/over-current protection, robust IP40 fan-less housing with Din-rail installation, wide operation temperature from -40°C to 75°C as well as high-level EMI/EMC capability. It is the best choice for heavy industrial factory, transportation, oil & gas, chemical, IP Surveillance and processing automation area where environmental conditions are harsh and critical


Technical specification

Model No.	LT-IS6012G-4GX8GT	
Interface	Fiber ports	Copper RJ45 ports
	4	8
Ethernet	8*10/100/1000Base-T 4*1000Base-X SFP	
Alarm port	One relay output for power failure. Alarm relay current carry ability: 1A@24VDC	
Standard	IEEE 802.3 10Base-T Ethernet IEEE 802.3u Fast Ethernet IEEE 802.3ab Gigabit Ethernet IEEE 802.3x Full-Duplex Flow Control IEEE 802.3az Energy Efficient Ethernet	
Dip Switch	<ol style="list-style-type: none"> 1. Link aggregation 2. Flow control 3. QoS(1-2 ports) 4. Broadcast storm restrain 	
LED Indicators		
P(Power indicator) Green	Off: the device is power off or failed	
	On: the device power on is normal	
S(System indicator) Red	Off: the chip is normal	
	On: the chip read/write is unnormal	

1-8 (Copper ports)	Green indicators	Yellow indicators
	Off: ports link down	Off: Port on 10/100M
	On: ports link up	On: Port on 1000M
	Blinking: data on TX/RX	
9-12 (Fiber ports) Green	Off: ports link down	
	On: ports link up	
	Blinking: data on TX/RX	
Power parameters		
Input voltage	12-58 VDC, redundant power input	
Input current	0.8A Max	
Total power consumption	Full loading ≤10W	
Connector	Removable 6-pin terminal block, pin 5/6 for relay alarm output	
Reverse polarity protection	Support	
Over-voltage protection	Support	
Over-current protection	Support	
Switching features		
Switching capacity	24G	
Packet forwarding rate	35.7 Mpps	
MAC address table	8K	
VLAN	4K	
Buffer	2M	
Forwarding delay	<5us	
Jumbo Frame	Support 10Kbytes	
MDX/MIDX	Support	
Watchdog	Support	
Network Topology		
Star topology	Support	

Bus topology	Support
Tree Topology	Support
Mechanical structure	
Case protection	IP40
Installation method	Din-rail
Dimension(W*D*H)mm	54*115*158mm
Weight	1.15 kg
Operating environment	
Operating temperature	-40°C~+75°C
Storage/transportation temperature	-40°C~+85°C
Relative humidity	5%~95% (non-condensing)
Industry standard	EMI: FCC Part 15B Class A
	Surge protection of power: IEC 61000-4-5 6KV/4KV (8/20us)
	Surge protection of Ethernet ports : IEC 61000-4-5 6KV/2KV (10/700us)
	RS: IEC 61000-4-3 80 MHz-1 GHz: 10 V/m
	EFT: IEC 61000-4-4 power interface: 4K; Ethernet ports: 2K
	CS: IEC 61000-4-6 10V
	ESD: IEC 61000-4-2 Level 4 (8K/15K)
	Shock: IEC 60068-2-27
	Free fall: IEC 60068-2-32
	Vibration: IEC 60068-2-6
Certification	CCC/CE/FCC/RoHS
Warranty	5 years

Structure diagram



Order information

Model	Description
LT-IS6012G-4GX8GT	Industrial Ethernet switch with 8*10/100/1000Base-T RJ45 ports and 4*1000Base-X SFP slots, DC12-58V input, redundant dual power supply, Din-rail installation. Operation temperature: -40°C ~ +75°C