

1*1G Fiber Port + 2*10/100/1000Base-T Simple Web Managed Ethernet Switch

LT-S3203G-1GX2GT/LT-S3203GP-1GX2GT

Overview

SmartByte LT-S3203G-1GX2GT/LT-S3203GP-1GX2GT are Layer 2 full gigabit managed switch, which features 2-port 10/100/1000Base-T RJ45 and 1*1G SFP ports or SC/ST fiber ports. It supports Layer 2 management with a high-performance switching architecture and offers wire-speed transportation capability for delivering a cost effective Gigabit Ethernet solution to meet the converged applications for enterprise customer's networks. LT-S3203GP-1GX2GT supports PoE function, which complies with IEEE802.3af and IEEE802.3at standard. It can provide the stable power supply for IP camera, PTZ camera, AP and PoE lighting equipments, etc through network cable.

Picture

Front

Back



SFP slot

Front

Back



SC transceiver (ST/FC optional)

	Support network storm suppression based on port bandwidth percentage	
PoE	/	Support IEEE802.3af (15.4W), IEEE802.3at (30W) 1/2+, 3/6- Support PoE management
VLAN	Support access mode Support trunk mode Support hybrid mode	
Port mirroring	Port Mirroring(many to one)	
Multicast	IGMP V1,V2,V3 IGMP snooping	
QoS	Ingress Port-based Rate-limit Egress Port-based Rate-limit	
Management and maintenance	Support user management and login authentication Support SNMPV2C/V3 Support web management, HTTP1.1, HTTPS Support Syslog and alarm grading Support RMON (Remote Monitoring) alarm, event and history record Support NTP Support TFTP Client Support Telnet Server Support SSH Server Support FTP, TFTP, WEB upgrading	
Dimension(mm)	140*88*28mm (Lx W x H)	
Fan	Fan-less design, natural cooling	
Power supply	DC input: 5-57V	DC input: 48-57V
Power consumption	Total power consumption ≤5W	Total power consumption (PoE full load) ≤65W
Temperature	Operation temperature: 0°C-50°C Storage temperature: -40°C-80°C	Operation temperature: 0°C-50°C Storage temperature: -40°C-80°C
Humidity	Operation humidity: 10%-90%RH Storage humidity: 5%-95%RH	

Model	Description
LT-S3203G-1GX2GT	1*1G SFP slot, 2*10/100/1000M adaptive RJ45 port, DC 5-57V input
LT-S3203GP-1GX2GT	1*1G SFP slot, 2*10/100/1000M adaptive RJ45 PoE port, DC 48-57V input
LT-S3203G-1GX2GT-SC20	1*1G SC fiber port(ST optional), 2*10/100/1000M adaptive RJ45 port, DC 5-57V input
LT-S3203GP-1GX2GT-SC20	1*1G SC fiber port(ST optional), 2*10/100/1000M adaptive RJ45 PoE port, DC 48-57V input