

8*10/100/1000Base-T Industrial PoE Switch

LT-IS6008GP-8GT



Features:

- 8*10/100/1000Base-T PoE ports
- DC 44~57V input, redundant power supply with polarity reverse/over-voltage protection
- Complies with IEEE802.3af PoE and IEEE802.3at PoE+ standard
- Dip switch function: 1.Port isolation; 2. 250m long distance; 3. QoS; 4.PoE watchdog
- Support 10K Bytes Jumbo frame
- Support 6KV surge protection and ESD: Air-15kV, Contact-8kV Protection
- IP40 fan-less and Din-rail hardware design
- Operation temperature: -40 °C ~+75 °C

Overview

The SmartByte LT-IS6008GP-8GT is the unmanaged industrial grade PoE switch with 8-port 10/100/1000-T RJ45 PoE. It complies with IEEE802.3af, IEEE802.3at standard PoE protocol, the Max power consumption can reach 30W (PoE+) per port. Moreover, it is featuring with port isolation, 250m long distance transmission mode(1-4 ports), QoS(1-2 ports) and PoE watchdog function, which all can be configured by the Dip switch on the top panel.

LT-IS6008GP-8GT is also a high cost-effective easy-to-use device, which provides essential industrial Ethernet networking function, such as wide range power input 44-57VDC, redundant power design with polarity reverse/over-voltage protection, robust IP40 fan-less housing with Din-rail installation, wide operation temperature from -40°C ~+75°C as well as high-level EMI/EMC capability and so on. It is the best choice for heavy industrial factory, transportation, oil & gas, chemical, IP Surveillance and processing automation area where environmental conditions exceed commercial product specifications.


Technical specification

Model No.	LT-IS6008GP-8GT	
Interface	Fiber port	Copper RJ45 ports
	0	8
Ethernet	8*10/100/1000Base-T RJ45 PoE	
Standard	IEEE 802.3 10Base-T Ethernet IEEE 802.3u Fast Ethernet IEEE 802.3ab Gigabit Ethernet IEEE 802.3x Full-Duplex Flow Control IEEE 802.3az Energy Efficient Ethernet IEEE 802.3af Power-Over-Ethernet IEEE 802.3at Power Over Ethernet plus PSE	
Dip Switch	<ol style="list-style-type: none"> 1. Port Isolation 2. 250m long distance mode(1-4 ports) 3. QoS(1-2 ports) 4. PoE watchdog 	
LED Indicators	P(Power indicator) Green	Off: the device is power off or failed
		On: the device power on is normal
	S(PoE usage indicator) Red	Off: total PoE usage < rated 50%

		Blinking: rated 50% < total PoE usage < rated 90%	
		On: total PoE usage ≥ rated 90%	
	1-8(Copper ports)	Green indicators	Yellow indicators
		Off: ports link down	Off: PoE not working
		On: ports link up	On: PoE working
Blinking: data on TX/RX			
Power parameters			
Input voltage	44-57VDC, redundant power input		
Input current	5.6A Max		
Total power consumption	Full loading without PoE ≤5W PoE power budget ≤240W		
Connector	Removable 4-pin terminal block		
Reverse polarity protection	Support		
Over-voltage protection	Support		
Switching features			
Switching capacity	16G		
Packet forwarding rate	23.8 Mpps		
MAC address table	16K		
VLAN	4K		
Buffer	2M		
Forwarding delay	<5us		
Jumbo Frame	Support 10Kbytes		
MDX/MIDX	Support		
Watchdog	Support		
Network Topology			
Star topology	Support		
Bus topology	Support		

Tree Topology	Support
Mechanical structure	
Case protection	IP40
Installation method	Din-rail
Dimension(W*D*H)mm	30*98*98mm
Weight	0.6kg
Operating environment	
Operating temperature	-40℃~+75℃
Storage/transportation temperature	-40℃~+85℃
Relative humidity	5%~95% (non-condensing)
Industrial Standard	Surge protection of power: IEC 61000-4-5 Level 4 (6KV/2KV) (8/20us)
	Surge protection of Ethernet ports: IEC 61000-4-5 Level 4 (6KV/2KV) (10/700us)
	DIP: IEC 61000-4-11 Level 3 (10V)
	ESD: IEC 61000-4-2 Level 4 (8K/15K)
	Shock: IEC 60068-2-27
	Free fall: IEC 60068-2-32
	Vibration: IEC 60068-2-6
Certification	CCC/CE/FCC/RoHS
Warranty	5 years

Structure diagram



Order information

Model	Description
LT-IS6008GP-8GT	8-port 10/100/1000Base-T industrial PoE switch with, complies with IEEE802.3af, IEEE802.3at standard, DC44-57V, redundant dual power supply, Din-rail installation. Operation temperature: -40°C ~ +75°C